

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (previously presented) A method for forming an integrated seat assembly, comprising:
 - providing a seat;
 - supporting from said seat a plurality of independent electronic components;
 - routing a single cable having a plurality of conductors into the seat, the cable supplying power for said independent electronic components and communication capability for at least one of the electronic components; and
 - using an electronics distribution system forming a portion of said seat to receive power from said cable and to supply power to each of said independent electronic components, and to interface with said one electronic component to enable communication with a subsystem located remotely from said seat.
2. (cancelled)
3. (original) The method of claim 1, wherein routing a single cable comprises routing a ribbon cable having a plurality of conductors into said seat.
4. (previously presented) The method of claim 1, wherein supporting a plurality of independent electronic components comprises supporting at least one of:
 - a video display unit, a telephone and a personal control unit.
5. (previously presented) A method for forming an integrated seat assembly, comprising:

providing a seat;
supporting from said seat a plurality of independent electronic components;
routing a single cable having a plurality of conductors into said seat;
using a selected first one of said conductors to directly supply power to at least one of said independent electronic components, and a second one of said conductors to interface with one of said independent electronic components; and
interfacing said cable with a distribution subsystem supported from said seat; and
using said distribution subsystem to supply signals to at least one of said independent electronic components and power to at least one of said independent electronic components.

6. (original) The method of claim 5, wherein using said cable comprises using a ribbon cable.

7. (original) The method of claim 5, wherein supporting a plurality of independent electronic components comprises supporting a video display unit.

8. (original) The method of claim 5, wherein supporting a plurality of independent electronic components comprises supporting a personal control unit.

9. (original) The method of claim 5, further comprising interfacing said distribution subsystem with said independent electronic components via a fiber optic coupling.

10. (original) The method of claim 5, further comprising interfacing said distribution subsystem with an audio interface.

11. (original) The method of claim 5, further comprising interfacing said distribution subsystem with a telephone.

12. (currently amended) A method for controlling electronic components located on a seat on a mobile platform, comprising:

routing a cable having a plurality of conductors along a leg portion of said seat;
interfacing said cable with a distribution subsystem supported by said seat; and
interfacing said distribution subsystem with a plurality of ~~said~~ independent electronic components to provide power to at least one of said electronic components and communication capability to at least one of said electronic components.

13. (cancelled)

14. (currently amended) The method of claim ~~13~~12, further comprising using said distribution subsystem to provide signals to at least one of said electronic components.

15. (original) The method of claim 12, wherein routing a cable comprises routing a ribbon cable.

16. (original) The method of claim 12, wherein supplying power comprises supplying power to a video display unit.

17. (original) The method of claim 12, wherein supplying power comprises supplying power to a personal control unit.

18. (original) The method of claim 12, further comprising interfacing said distribution subsystem with an audio interface.

19. (original) The method of claim 12, further comprising interfacing said distribution subsystem with a telephone.

20. (original) The method of claim 12, further comprising locating said distribution subsystem adjacent a seat portion of said seat.